

ITW Engineered Polymers

SAFETY DATA SHEET MA2045 Adhesive

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MA2045 Adhesive
Product number IT196

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Adhesive.

1.3. Details of the supplier of the safety data sheet

Supplier ITW Engineered Polymers
Bay 150
Shannon Industrial Estate
Shannon
Co. Clare

+353 (0)61 471 299
+353 (0)61 471 285
mail@itwep.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture


Classification

Physical hazards Flam. Liq. 2 - H225
Health hazards Eye Irrit. 2 - H319 Skin Sens. 1 - H317
Environmental hazards Not Classified

Classification (67/548/EEC or 1999/45/EC) Xi;R36/37/38. R43. F;R11. N;R51/53.

2.2. Label elements

Pictogram



Signal word

Danger

Hazard statements

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H225 Highly flammable liquid and vapour.

MA2045 Adhesive

| | |
|---|--|
| Precautionary statements | <p>P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.</p> <p>P280 Wear protective gloves/protective clothing/eye protection/face protection.</p> <p>P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.</p> <p>P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P333+P313 If skin irritation or rash occurs: Get medical advice/attention.</p> <p>P501 Dispose of contents/container in accordance with national regulations.</p> |
| Contains | METHYL METHACRYLATE |
| Supplementary precautionary statements | <p>P233 Keep container tightly closed.</p> <p>P240 Ground/bond container and receiving equipment.</p> <p>P241 Use explosion-proof electrical equipment.</p> <p>P242 Use only non-sparking tools.</p> <p>P243 Take precautionary measures against static discharge.</p> <p>P261 Avoid breathing vapour/spray.</p> <p>P264 Wash contaminated skin thoroughly after handling.</p> <p>P272 Contaminated work clothing should not be allowed out of the workplace.</p> <p>P302+P352 IF ON SKIN: Wash with plenty of water.</p> <p>P321 Specific treatment (see medical advice on this label).</p> <p>P337+P313 If eye irritation persists: Get medical advice/attention.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p> <p>P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.</p> <p>P403+P235 Store in a well-ventilated place. Keep cool.</p> |

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

| | |
|-------------------------|--|
| DIBUTYL MALEATE | 10-30% |
| CAS number: 105-76-0 | |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Skin Sens. 1 - H317 | - |
| BENZOYL PEROXIDE | 10-30% |
| CAS number: 94-36-0 | EC number: 202-327-6 |
| Classification | Classification (67/548/EEC or 1999/45/EC) |
| Org. Perox. B - H241 | E;R3 O;R7 Xi;R36 R43 |
| Eye Irrit. 2 - H319 | |
| Skin Sens. 1 - H317 | |

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|----------------------------|---|
| General information | In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). |
|----------------------------|---|

MA2045 Adhesive

| | |
|---------------------|---|
| Inhalation | Move affected person to fresh air at once. For breathing difficulties, oxygen may be necessary. Get medical attention if any discomfort continues. |
| Ingestion | Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. |
| Skin contact | Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if irritation persists after washing. |
| Eye contact | Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|----------------------------|---|
| General information | The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
|----------------------------|---|

4.3. Indication of any immediate medical attention and special treatment needed

| | |
|-----------------------------|---|
| Notes for the doctor | No specific recommendations. If in doubt, get medical attention promptly. |
|-----------------------------|---|

SECTION 5: Firefighting measures

5.1. Extinguishing media

| | |
|---------------------------------------|---|
| Suitable extinguishing media | Extinguish with the following media: Carbon dioxide (CO ₂). Dry chemicals. Foam. Water spray. |
| Unsuitable extinguishing media | Do not use water, if avoidable. |

5.2. Special hazards arising from the substance or mixture

| | |
|-------------------------|--|
| Specific hazards | Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . |
|-------------------------|--|

5.3. Advice for firefighters

| | |
|--|---|
| Protective actions during firefighting | Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. |
| Special protective equipment for firefighters | Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|-----------------------------|--|
| Personal precautions | Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Use suitable respiratory protection if ventilation is inadequate. |
|-----------------------------|--|

6.2. Environmental precautions

| | |
|----------------------------------|--|
| Environmental precautions | Do not discharge into drains or watercourses or onto the ground. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body. |
|----------------------------------|--|

6.3. Methods and material for containment and cleaning up

MA2045 Adhesive

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Provide adequate ventilation. Keep away from heat, sparks and open flame. Handle and open container with care. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep away from heat, sparks and open flame.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

BENZOYL PEROXIDE

Long-term exposure limit (8-hour TWA): WEL 5 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

The following protection should be worn: Chemical splash goggles.

Hand protection

Use protective gloves. Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact. Wear chemical protective suit.

Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Wash hands at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Wash promptly if skin becomes contaminated.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn.

MA2045 Adhesive

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

| | |
|---------------------------------|-------------------------------------|
| Appearance | Paste. |
| Colour | White/off-white. |
| pH | pH (diluted solution): 7 |
| Melting point | -47.7°C |
| Initial boiling point and range | 100.5°C @ |
| Flash point | 10 degree C°C TCC (Tag closed cup). |
| Evaporation rate | 3 (Butyl Acetate=1) |
| Vapour pressure | 28 mm Hg @ °C |
| Vapour density | >1 |
| Relative density | 0.93 - 1.05 @ °C |
| Solubility(ies) | |
| Auto-ignition temperature | Not determined. |

9.2. Other information

| | |
|---------------------------|---|
| Other information | Not available. |
| Volatility | «184» |
| Volatile organic compound | This product contains a maximum VOC content of <50 g/litre. |

SECTION 10: Stability and reactivity

10.1. Reactivity

| | |
|------------|----------------------------------|
| Reactivity | Strong oxidising agents. Amines. |
|------------|----------------------------------|

10.2. Chemical stability

| | |
|-----------|---|
| Stability | Stable at normal ambient temperatures and when used as recommended. |
|-----------|---|

10.3. Possibility of hazardous reactions

| | |
|------------------------------------|----------------------|
| Possibility of hazardous reactions | Will not polymerise. |
|------------------------------------|----------------------|

10.4. Conditions to avoid

| | |
|---------------------|---|
| Conditions to avoid | Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight. |
|---------------------|---|

10.5. Incompatible materials

| | |
|--------------------|---|
| Materials to avoid | Strong mineral acids. Strong oxidising agents. Alkalis - organic. Amines. |
|--------------------|---|

10.6. Hazardous decomposition products

| | |
|----------------------------------|--|
| Hazardous decomposition products | Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Aldehydes. Acids. |
|----------------------------------|--|

SECTION 11: Toxicological information

11.1. Information on toxicological effects

MA2045 Adhesive

| | |
|---|--|
| Inhalation | No significant hazard at normal ambient temperatures. Heating may generate the following products: Irritating gases or vapours. |
| Ingestion | Nausea, vomiting. Diarrhoea. |
| Skin contact | Irritating to skin. May cause sensitisation by skin contact. Prolonged or repeated exposure may cause severe irritation. May cause sensitisation or allergic reactions in sensitive individuals. |
| Eye contact | Irritating to eyes. Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. |
| Acute and chronic health hazards | The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals. |

SECTION 12: Ecological Information

| | |
|--|--|
| Ecotoxicity | Avoid releasing into the environment. |
| <u>12.1. Toxicity</u> | |
| Toxicity | Not considered toxic to fish. |
| Acute toxicity - fish | LC ₅₀ , 96 hours: BPO:96 hr, LC50 GUPPY (SEMI-STATIC)=2.0 mg/l mg/l, Fish |
| <u>12.2. Persistence and degradability</u> | |
| Persistence and degradability | The degradability of the product is not known. |
| <u>12.3. Bioaccumulative potential</u> | |
| Bioaccumulative potential | No data available on bioaccumulation. |
| <u>12.4. Mobility in soil</u> | |
| Mobility | Do not discharge into drains or watercourses or onto the ground. |
| <u>12.5. Results of PBT and vPvB assessment</u> | |
| Results of PBT and vPvB assessment | This product does not contain any substances classified as PBT or vPvB. |
| <u>12.6. Other adverse effects</u> | |
| Other adverse effects | Not available. |

SECTION 13: Disposal considerations

| | |
|---|---|
| <u>13.1. Waste treatment methods</u> | |
| General information | When handling waste, the safety precautions applying to handling of the product should be considered. |
| Disposal methods | Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. |
| Waste class | 08 04 99 |

SECTION 14: Transport information

| | |
|-------------------------------|-----------------------------|
| General | No other information known. |
| <u>14.1. UN number</u> | |
| UN No. (ADR/RID) | 1133 |
| UN No. (IMDG) | 1133 |

MA2045 Adhesive

UN No. (ICAO) 1133

14.2. UN proper shipping name

Proper shipping name (ADR/RID) ADHESIVES

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (ADN) ADHESIVES

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID subsidiary risk

ADR/RID label 3

IMDG class 3

IMDG subsidiary risk

ICAO class/division 3

ICAO subsidiary risk

Transport labels

14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ICAO packing group II

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

Emergency Action Code •3YE

Hazard Identification Number (ADR/RID) 33

Tunnel restriction code (D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information required.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

MA2045 Adhesive

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Water hazard classification WGK 2

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 20/04/2015

Revision 7

Supersedes date 08/04/2015

Risk phrases in full

- R11 Highly flammable.
- R21/22 Harmful in contact with skin and if swallowed.
- R35 Causes severe burns.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R37 Irritating to respiratory system.
- R37/38 Irritating to respiratory system and skin.
- R43 May cause sensitisation by skin contact.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Hazard statements in full

- H225 Highly flammable liquid and vapour.
- H302 Harmful if swallowed.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.