

# Engineered Polymers

## SAFETY DATA SHEET PC120 PRIMER

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product identifier

Product name PC120 PRIMER  
Product No. Z0050

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Primer.

#### 1.3. Details of the supplier of the safety data sheet

Supplier ITW Engineered Polymers  
Bay 150  
Shannon Industrial Estate  
Shannon  
Co. Clare  
+353 (0)61 471 299  
+353 (0)61 471 285  
mail@itwep.com

#### 1.4. Emergency telephone number

+44(0)1235 239 670 (24h)

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 2 - H225
Human health	Eye Irrit. 2 - H319; STOT SE 3 - H336
Environment	Not classified.

Classification (1999/45/EEC) Xi; R36. F; R11. R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

Human health

Contains organic solvents which in case of overexposure may depress the central nervous system causing dizziness and intoxication.

#### 2.2. Label elements

Label In Accordance With (EC) No. 1272/2008



Hazard Statements

H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplementary Precautionary Statements

P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.

## PC120 PRIMER

P241	Use explosion-proof electrical/ventilating/lighting/.../equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P264	Wash ... thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P313	Get medical advice/attention.
P337	If eye irritation persists:
P370+378	In case of fire: Use ... for extinction.
P403+233	Store in a well-ventilated place. Keep container tightly closed.
P403+235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container to ...

### 2.3. Other hazards

This product does not contain any PBT or vPvB substances.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

PROPAN-2-OL	60-100%
CAS-No.: 67-63-0	EC No.: 200-661-7
Classification (EC 1272/2008)	Classification (67/548/EEC)
Flam. Liq. 2 - H225	F;R11
Eye Irrit. 2 - H319	Xi;R36
STOT SE 3 - H336	R67

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

General information

Do not breathe vapour/spray. Avoid contact with skin and eyes. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).

Inhalation

Move the exposed person to fresh air at once. Contact physician if discomfort continues.

Ingestion

Do not induce vomiting. Drink plenty of water. Get medical attention. NEVER MAKE AN UNCONSCIOUS PERSON VOMIT OR DRINK FLUIDS!

Skin contact

Remove affected person from source of contamination. Wash skin thoroughly with soap and water for several minutes. Contact physician if irritation persists.

Eye contact

Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Contact physician if irritation persists.

### 4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure.

# PC120 PRIMER

## **4.3. Indication of any immediate medical attention and special treatment needed**

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

## **SECTION 5: FIREFIGHTING MEASURES**

### **5.1. Extinguishing media**

Extinguishing media

Fire can be extinguished using: Carbon dioxide or dry powder. Water spray, fog or mist.

### **5.2. Special hazards arising from the substance or mixture**

Specific hazards

HIGHLY FLAMMABLE! When heated and in case of fire, irritating vapours/gases may be formed. May travel considerable distance to source of ignition and flash back.

### **5.3. Advice for firefighters**

Special Fire Fighting Procedures

Avoid breathing fire vapours. Keep up-wind to avoid fumes. Avoid water in straight hose stream; will scatter and spread fire. Keep run-off water out of sewers and water sources. Dike for water control.

Protective equipment for fire-fighters

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### **6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective clothing as described in Section 8 of this safety data sheet. Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Eliminate all sources of ignition. Take precautionary measures against static discharges.

### **6.2. Environmental precautions**

Do not allow ANY environmental contamination. Do not discharge into drains, water courses or onto the ground. Spillages or uncontrolled discharges into watercourses must be IMMEDIATELY alerted to the Environmental Agency or other appropriate regulatory body.

### **6.3. Methods and material for containment and cleaning up**

Absorb spillage with non-combustible, absorbent material. Transfer to a container for disposal. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### **6.4. Reference to other sections**

Wear protective clothing as described in Section 8 of this safety data sheet. See section 11 for additional information on health hazards.

## **SECTION 7: HANDLING AND STORAGE**

### **7.1. Precautions for safe handling**

Use only in well-ventilated areas. Avoid contact with skin and eyes. Keep away from heat, sparks and open flame. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Observe good chemical hygiene practices.

### **7.2. Conditions for safe storage, including any incompatibilities**

Store in tightly closed original container in a dry, cool and well-ventilated place.

### **7.3. Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

### **8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
PROPAN-2-OL	WEL	400 ppm	999 mg/m3	500 ppm	1250 mg/m3	

WEL = Workplace Exposure Limit.

# PC120 PRIMER

Ingredient Comments

WEL = Workplace Exposure Limits

## 8.2. Exposure controls

Protective equipment



Process conditions

Provide eyewash, quick drench.

Engineering measures

Provide adequate general and local exhaust ventilation.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

Hand protection

Use protective gloves made of: Rubber or plastic.

Eye protection

Wear approved chemical safety goggles where eye exposure is reasonably probable.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving work place.

Skin protection

Wear apron or protective clothing in case of contact.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Red.
Odour	Solvent.
Initial boiling point and boiling range (°C)	83
Melting point (°C)	-88
Relative density	0.81 20 °C
Vapour pressure	32 mmHg 20
pH-Value, Conc. Solution	8.5 @ 20 °C
Flash point (°C)	12
Flammability Limit - Lower(%)	2
Flammability Limit - Upper(%)	12

### 9.2. Other information

No information required.

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Strong oxidising agents.

### 10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

### 10.3. Possibility of hazardous reactions

Not applicable.

### 10.4. Conditions to avoid

## PC120 PRIMER

Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time.

### **10.5. Incompatible materials**

Materials To Avoid

Avoid contact with oxidising agents. Contact with peroxides. Other metals or alloys.

### **10.6. Hazardous decomposition products**

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: TOXICOLOGICAL INFORMATION

### **11.1. Information on toxicological effects**

Toxic Dose 1 - LD 50  
5045 mg/kg (oral rat)  
Toxic Conc. - LC 50  
22627 ppm/4h (inh-rat)

Inhalation

Vapours may cause drowsiness and dizziness.

Skin contact

Irritating to skin.

Eye contact

Irritating to eyes.

Toxicological information on ingredients.

#### **PROPAN-2-OL (CAS: 67-63-0)**

Toxic Dose 1 - LD 50  
5054 mg/kg (oral rat)  
Toxic Dose 2 - LD 50  
3600 mg/kg (oral-mouse)

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Do not release into the environment.

### **12.1. Toxicity**

Acute Fish Toxicity

Not considered toxic to fish.

### **12.2. Persistence and degradability**

Degradability

The degradability of the product has not been stated.

### **12.3. Bioaccumulative potential**

Bioaccumulative potential

No data available on bioaccumulation.

### **12.4. Mobility in soil**

Mobility:

Do not discharge into drains, water courses or onto the ground.

### **12.5. Results of PBT and vPvB assessment**

This product does not contain any PBT or vPvB substances.

### **12.6. Other adverse effects**

Not available.

# PC120 PRIMER

## SECTION 13: DISPOSAL CONSIDERATIONS

### General information

When handling waste, consideration should be made to the safety precautions applying to handling of the product.

### 13.1. Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements.

Waste Class

08 04 09

## SECTION 14: TRANSPORT INFORMATION

General No other information noted.

### 14.1. UN number

UN No. (ADR/RID/ADN) 1219

UN No. (IMDG) 1219

UN No. (ICAO) 1219

### 14.2. UN proper shipping name

Proper Shipping Name ISOPROPANOL (ISOPROPYL ALCOHOL)

### 14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

IMDG Class 3

ICAO Class/Division 3

Transport Labels



### 14.4. Packing group

ADR/RID/ADN Packing group II

IMDG Packing group II

ICAO Packing group II

### 14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant

No.

### 14.6. Special precautions for user

EMS F-E, S-D

Emergency Action Code 2YE

Hazard No. (ADR) 33

### 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

# PC120 PRIMER

Not applicable.

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

Water hazard classification

WGK 1

### 15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

## SECTION 16: OTHER INFORMATION

Revision Date	11/02/2015
Revision	11
Supersedes date	05/12/2014
Date	05/12/2014
Risk Phrases In Full	
R11	Highly flammable
R36	Irritating to eyes.
R67	Vapours may cause drowsiness and dizziness.
Hazard Statements In Full	
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

### Disclaimer

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.